

(12)

**EUROPEAN PATENT APPLICATION**

(21) Application number: **84307634.0**

(51) Int. Cl.<sup>4</sup>: **G 01 N 33/543**

(22) Date of filing: **06.11.84**

(30) Priority: **07.11.83 CA 440575**

(43) Date of publication of application:  
**12.06.85 Bulletin 85/24**

(64) Designated Contracting States:  
**AT BE CH DE FR GB IT LI LU NL SE**

(71) Applicant: **ALLELIX INC.**  
**6850 Goreway Drive**  
**Mississauga Ontario, L4V 1P1(CA)**


(72) Inventor: **Chandler, Howard M.**  
**6850 Goreway Drive**  
**Mississauga Ontario, L4V 1P1(CA)**

(74) Representative: **Hale, Stephen Geoffrey et al,**  
**J.Y. & G.W. Johnson Furnival House 14/18 High Holborn**  
**London WC1V 6DE(GB)**

(54) **Device and method for performing qualitative enzyme immunoassays.**

(57) A device for performing qualitative enzyme immunoassays comprises at least one tube (11) having antibody, antigen or hapten attached to an internal surface thereof. A first syringe (17) is connectable to a first end of the tube or tubes (11) and supplies a flow of test liquid therethrough. A second syringe (18) having a two piston arrangement (33, 35) is connected to the tube so as to allow a first wash solution followed by an enzyme conjugate solution to be flowed therethrough. Finally a third syringe (19), also having a two piston configuration (33, 35), is connected to the tube (11) so as to allow a second wash solution followed by an enzyme substrate and metabolite indicator solution to be flowed therethrough. The device can be used in a method in which the test liquid is flowed through the tube for about 1 minute, the first wash solution is then flowed through the tube followed by an enzyme conjugate solution, followed after an incubation period of at least one minute by a second wash solution and a solution containing enzyme substrate and enzyme metabolite indicator.

./...



**FIG. 1**

Device and method for performing qualitative enzyme  
immunoassays

---

The present invention relates to a device and method for performing qualitative enzyme immunoassays. The invention provides a portable compact device which may be used by an untrained person or which is suitable for use by medical personnel in the field or  
5 elsewhere when a quick determination is required for diagnostic purposes. The device is particularly suitable for testing urine samples but also may be used for performing enzyme immunoassays using a wide variety of test solutions.

In its preferred form, the invention may be used to detect the  
10 presence of an antigen or hapten in urine or serum. This assay is accomplished by the known method of contacting the sample with an antibody specific to the antigen or hapten being assayed for, which antibody is attached to a solid support such as the wall of a tube. Antigen which is captured by the fixed antibody is then  
15 detected by contacting the solid phase with an antibody/enzyme conjugate followed by treatment with an enzyme substrate and suitable indicator.

The present device is capable of detecting the substance being assayed for in lower concentration and with much greater speed  
20 than has heretofore been possible with prior art devices. Prior devices for the detection of an antigen or hapten employ an antibody attached to a solid support which is contacted sequentially with static volumes of test liquid, conjugate and substrate/indicator solutions. A period of incubation must be  
25 observed for each of these contacting steps as the reactions involved are diffusion controlled. That is, the reactions take place only at the surface of the solid support and sufficient time must elapse to enable enough antigen to migrate to the reaction vessel wall to give a positive test result. Increasing  
30 the surface area to volume ratio by carrying out these reactions in a tube having a small bore reduces incubation periods to about ten minutes each.

The present device employs a method whereby a continuous flow of the various reactive solutions are passed through a tube having  
35 the antibody affixed thereto so that the principles of affinity

capture and concentration are utilized. That is, the reaction at the tube wall is forced to completion quickly by continuously bathing the solid reactant with a solution having a constant concentration of the co-reactant. This also means that the sensitivity of the assay is increased since a much lower concentration of co-reactant in the test sample can be detected by this flow through method. Thus, the present invention provides significant advantages over the devices and methods previously known. In the case of a pregnancy test, discussed in detail below, the assay for the presence of human chorionic gonadotropin (HCG) in the urine may be carried out as quickly as about three minutes using the device of the invention as compared to prior art pregnancy test devices which require 20 to 120 minutes to perform the assay. Also, the present device is much simpler to use than prior devices and many fewer operations need be performed when using the device in order to carry out the assay than is required by prior devices.

It should also be clear that the present device may be used generally for all enzyme immunoassays and should not be construed as being restricted to the detection of antigens or haptens in the manner just summarized. Without limiting the possible applications of the present invention, the device may be used as suggested to detect antigen or hapten in an antibody sandwich-type assay, or a double antibody sandwich antigen assay may be used, or a competitive antigen assay can be performed. When detection of antibody is desired, the device can be used to do a sandwich-type assay or a double antibody sandwich antibody assay. For example, in an antigen assay for  $\pm$  hepatitis subunit or virus using the double antibody sandwich antigen assay, the solid phase comprises anti-hepatitis Ab type 1 (e.g. sheep), the second antibody used is anti-hepatitis Ab type 2 (e.g. rabbit), and the conjugate is anti-type 2 Ab/enzyme.

The present device is especially suitable if a large volume of test sample is available, such as urine. A particularly suitable assay using the present device is a test for the presence of HCG (human chorionic gonadotropin) in urine to determine pregnancy.

Because of the aforementioned features, pregnancy can be quickly detected at an early stage by the woman herself using the present device.

Accordingly, the invention provides a device for performing an enzyme immunoassay, comprising at least one tube having an antibody, antigen or hapten attached to an internal surface thereof. A first syringe is connectable to a first end of tube or tubes for supplying a flow of test liquid therethrough, and a second syringe is connected to the first end of the tube or tubes for supplying a flow of a first wash solution followed immediately by a flow of enzyme conjugate containing solution therethrough, said second syringe having a first unattached piston and a second piston attached to a plunger, the first piston being positioned to separate the first wash solution from the conjugate solution, and said syringe also having a wall with a groove therein connecting the syringe outlet with the conjugate solution only when the first piston is fully depressed. A third syringe is connected to the first end of the tube or tubes for supplying a flow of a second wash solution followed immediately by a flow of solution containing enzyme substrate and enzyme metabolite indicator therethrough, said third syringe having a structure like that of the second syringe.

The invention also provides a method for performing an enzyme immunoassay, comprising the steps of:

; attaching an antibody antigen or hapten to an internal surface of a tube;

flowing a test liquid through the tube for about one minute;

flowing a first wash solution through the tube to flush out the test liquid;

flowing an enzyme conjugate solution through the tube followed by an incubation period of at least one minute;

flowing a second wash solution through the tube at the end of the incubation period to flush out the enzyme conjugate solution; and

- 5 flowing a solution containing enzyme substrate and enzyme metabolite indicator through the tube followed by an incubation period of up to about 10 minutes.

A preferred embodiment of the invention will be described with reference to the drawings in which:

- 10 Figure 1 is a perspective view partially cut away of the testing device;

Figure 2 is a perspective view from below the device with the bottom plate removed; and

- Figure 3 is a cut away view of an alternate double piston syringe 15 which may be used in the present device.

- While the present device may be used for a number of different assay applications, and indeed may be used for performing multiple assays on a single test sample, the preferred embodiment hereinafter described relates to the use of the invention for
- 20 testing for pregnancy by assaying for the presence of HCG (human chorionic gonadotropin) in urine.

- The preferred testing device of the invention comprises a body 10 in which is centrally disposed a tube 11 having applied to the inner wall thereof a coating of anti-HCG, i.e. HCG antibody. The
- 25 anti-HCG coating is preferably covalently bonded to the tube wall, but it may be affixed by adsorption. For the purpose of providing a control, the tube 11 is connected in series to a plain uncoated tube 12. The control tube 12 is in turn connected to a waste reservoir 15 as described below. In order to make
  - 30 good use of the advantages of the flow through technique, it is

0144162

desirable to have a surface area to volume ratio in the tube 11 as large as is practical given the various parameters surrounding the manufacture and use of the preferred device. Thus, a tube 11 on the order of about 25 mm in length having a bore of about 1 mm in diameter is quite suitable in the present context.

The various solutions required to perform the assay are passed sequentially through the tubes 11 and 12 by means of syringes 17, 18 and 19. A test sample syringe 17 is removable from a receptacle 21 therefor which is integral with the body 10. The test sample syringe 17 comprises a body 23 having an outlet 24 at one end and a plunger 25 having a piston 26 attached at an end thereof which may move slidably within the syringe body 23 to fill and empty the syringe 17 with a liquid test sample. A urine sample of about 5 ml is reasonable for use in the particular pregnancy test device described herein.

The body 10 preferably has two additional syringes 18 and 19 integral therewith. However, the preferred device may comprise removable syringes 18 and 19, and indeed this may be desirable in certain circumstances. The syringe 18 comprises a receptacle 30 having an outlet 31 at its lower end and a groove 32 communicating with the outlet 31 in the wall thereof. The syringe receptacle 30 is provided with an unattached piston 33 and a plunger 34 having a piston 35 attached at one end thereof. The free piston 33 is used to separate two solutions contained within the syringe receptacle 30, one solution contained in an upper portion 36 of the syringe 18 between the free piston 33 and the plunger 34, and the other solution contained in a lower portion 37 between the free piston 33 and the outlet 31. The final syringe 19 is of a structure identical to that of syringe 18.

The outlets of the syringes 17, 18 and 19 are connected to the lower end of the tube 11 by means of channels 40, 41 and 42 formed in the base 43 of the body 10 (Fig. 2). The channel 40 connects an opening 45 for the outlet 24 of the sample syringe 17 to an opening 46 for the tube 11. Likewise channels 41 and 42 connect the outlets 31 of syringes 18 and 19 with the opening

0144162

46. An opening 48 is provided in the base 43 for the outlet end of the control tube 12 which is in turn connected to the waste reservoir 15 by means of a channel 49. Finally, a vent shaft 51 is provided in the body 10, the lower end of which is connected to the waste reservoir 15 by means of a slot 52 in the body 10. The base 43 comprises a flat surface which fits flush against an unbroken flat surface 55 of a bottom plate 56 for the device.

For the purpose of providing a pregnancy testing device, the syringe 18 is filled with a solution containing an enzyme/anti-HCG conjugate in the upper portion 36. A urease/anti-HCG conjugate is preferred in this regard. The lower portion 37 of the syringe 18 is filled with a wash solution compatible with the subsequently added conjugate solution.

The upper portion 36 of the syringe 19 is filled with a solution containing substrate for the enzyme of the conjugate and an indicator to detect the conversion of substrate by the enzyme in the tube 11. Preferably, the substrate is urea which is metabolized by the urease of the conjugate to give ammonia and carbon dioxide. The pH rise caused by the release of ammonia can then be detected by a pH indicator such as bromthymol blue. The lower portion 37 of the syringe 19 is filled with a suitable wash solution, which in particular device described herein is the same as in the syringe 18.

To operate the present device to determine a suspected pregnancy, the syringe 17 is filled with a urine sample and inserted into the receptacle 21. With the syringe 17 in place in the device, the plunger 25 is slowly depressed so that the urine sample flows through the tubes 11 and 12 over a period of about one minute. Next, the plunger 34 of the syringe 18 is fully depressed causing a first wash solution to flow through the tubes 11 and 12 thereby washing out retained urine sample, and then causing a flow of enzyme/antibody conjugate solution to pass through the tubes 11 and 12. An incubation period of about two minutes should be observed at this point to allow the conjugate time to react with any HCG captured by the anti-HCG held at the tube 11 wall. If



required, a longer incubation period may be used to increase the sensitivity of an assay.

After the incubation period has elapsed, the plunger 34 of the syringe 19 is fully depressed causing a second wash solution to flush the conjugate from the tubes 11 and 12, and then causing a flow of substrate/indicator solution to pass through the tubes 11 and 12. If the woman is pregnant and HCG is therefore present, the captured enzyme in the tube 11 will metabolize the substrate and cause the indicator to be activated. Use of a color change indicator such as bromthymol blue in a urea/urease system will give a change in the color of the liquid in the tube 11 from yellow to blue. This color change can be compared with the color in the control tube 12 which should remain yellow. A relatively high concentration of HCG in the test sample will give a color indication almost immediately, however, a low concentration of HCG will require up to 10 minutes to give a positive indicator response.

Because of the aforementioned features of the present device, low levels of HCG on the order of 50 mIU/ml can be detected. This is important so that pregnancy can be diagnosed at an early stage and so that a quick test can be carried out to reliably indicate an ectopic pregnancy.

The preferred enzyme for use in the pregnancy test device of the invention is urease because it is easily detected by the pH rise caused by metabolism of its substrate urea. Also, urea is stable in aqueous solution for at least six months at room temperature. This is in contrast to other substrates such as hydrogen peroxide, used with horseradish peroxidase, which breaks down rather quickly. However, without refrigeration, urea in water will eventually break down thereby making the device unusable. To provide a device having a long shelf life, i.e. two years, at room temperature, the syringe 19 may be modified as shown in Figure 3.

- 8 -

- The modified syringe 19 has a plunger 60 equipped with a rod 61 slidably disposed longitudinally within it. The rod 61 has a piston 62 affixed at its lower end, and the piston 62 has a piercing member 63 protruding from the lower surface thereof.
- 5 The plunger 60 has a rupture membrane 65 covering the opening at its lower end, and the chamber 66 created by the membrane 65, the interior of the plunger 60 and the lower end of the rod 61 provides a space for storing powdered urea or other unstable component which may be used in another application.
- 10 When the pregnancy test is to be performed, the rod 61 is depressed causing the piercing member 63 to rupture the membrane 65 thereby dispensing the powdered urea into the aqueous medium in the upper portion 36 of the syringe 19. The urea will quickly dissolve and the test can be immediately conducted
- 15 in the manner described above. The piercing member 63 may also assist the dissolution of the powdered urea by causing a portion of it to be retained about the teeth 67 thereof. The retention aids in evenly distributing the powdered urea through the aqueous medium for rapid dissolution.
- 20 A further alternate embodiment for the syringe 19 (not shown) would incorporate a secondary syringe of conventional construction positioned snugly within the upper portion of the bore of the syringe 19 and having the end nipple thereof plugged by the free piston 33. The space created between the
- 25 top of the piston 33 and the end of the secondary syringe can accommodate the substrate powder while the secondary syringe itself is provided with the aqueous substrate medium. In operation, pressure exerted by the plunger 34 will cause the free piston 33 to pop off the end of the secondary syringe and
- 30 travel down the bore of the syringe 19 forcing the wash solution through the tubes 11 and 12. The substrate will dissolve in the aqueous medium discharged from the secondary syringe. Continued pressure on the plunger 34 upon reaching the end of the secondary syringe will force the entire
- 35 secondary syringe assembly downward causing the substrate solution to flow out of the syringe 19 as previously described.

As mentioned above, syringes 18 and 19 may also be removable, and as such may have a body and outlet as shown in Figure 1 for the syringe 17. This arrangement would be applicable when different wash solutions are required in the lower portions 37 of the syringes 18 and 19 since in the preferred device just described, such wash solutions are in communication with one another.

Finally, in its commercial form, the present device will be sold with a protective hard cover member 70 as shown in Fig. 1. The cover member 70 will fit snugly about a peripheral shoulder 71 about the bottom portion of the body 10 thereby protecting all of the components of the device prior to use. A projection (not shown) within the cover 70 may be desirable to plug the vent 51 while in storage thus preventing evaporation of wash solutions in the lower portions 37 of the syringes 18 and 19. Removal of the cover 70 unplugs the vent 51 in readiness for performance of the test.

CLAIMS

1. A device for performing an enzyme immunoassay, comprising: at least one tube (11) having an antibody, antigen or hapten attached to an internal surface thereof; a first syringe (17) connectable to a first end of  
5 the one or more tubes (11) for supplying a flow of test liquid therethrough; a second syringe (18) connected to the first end of the one or more tubes (11) for supplying a flow of a first wash solution followed immediately by a flow of enzyme conjugate containing  
10 solution therethrough, said second syringe (18) having a first unattached piston (33) and a second piston (35) attachable to a plunger (34), the first piston (33) being positioned to separate the first wash solution from the conjugate solution, said syringe (18) also  
15 having a wall (30) with a groove (32) therein connecting the syringe outlet (31) with the conjugate solution only when the first piston (33) is fully depressed; and a third syringe (19) connected to the first end of the one or more tubes (11) for supplying a flow  
20 of a second wash solution followed immediately by a flow of solution containing enzyme substrate and enzyme metabolite indicator therethrough, said third syringe (19) having a first unattached piston (33) and a second piston (35) attachable to a plunger (34), the first  
25 piston (33) being positioned to separate the second wash solution from the substrate, said syringe (19) also having a wall (30) with a groove (32) therein connecting the syringe outlet (31) with the substrate and indicator in solution only when the first piston  
30 (33) is fully depressed.

2. A device as claimed in claim 1, wherein the antibody, antigen or hapten is covalently bonded to the internal surface of the at least one tube (11).

3. A device as claimed in claim 1 or 2, further

comprising a control tube (12) not having any antibody, antigen or hapten attached to an internal surface thereof.

4. A device as claimed in any of claims 1 to 3, wherein the first syringe (17) is detachable therefrom and the second and third syringes (18, 19) are integral therewith.

5. A device as claimed in any of claims 1 to 4, further comprising means (15) for receiving and storing liquids which have flowed through the one or more tubes.

6. A device as claimed in claim 5, wherein the means for receiving and storing liquids comprises a reservoir (15) formed integrally with the device.

7. A device as claimed in any of claims 1 to 6, wherein the device is a pregnancy test kit having human chorionic gonadotropin antibody (anti-HCG) attached to the internal surface of the tube, the enzyme conjugate being urease/anti-HCG, the enzyme substrate being urea, and the enzyme metabolite indicator being bromthymol blue, particularly a device for use with urine or serum as the test liquid.

8. A device as claimed in any of claims 1 to 7, further comprising a third syringe (19) wherein the plunger (60) thereof is provided with a rod (61) slidably disposed longitudinally within it, said rod (61) having a piston (62) affixed at its lower end, the piston (62) being equipped with a piercing member (63) protruding from the lower surface thereof and the plunger (60) having a rupture membrane (65) covering an opening at its lower end, said membrane (65), the interior of the plunger (60) and the lower end of the rod (61) defining a chamber (66).

- 12 -

9. A device as claimed in claim 8, wherein the device is a pregnancy test kit having human chorionic gonadotropin antibody (anti-HCG) attached to the internal surface of the tube, the enzyme conjugate being urease/  
5 anti-HCG, the enzyme substrate being urea contained in powder form in said chamber and the indicator being brom-thymol blue.

10. A device as claimed in any of claims 1 to 7, further comprising a third syringe (19) wherein a secondary syringe is positioned snugly within the upper portion  
10 thereof, said secondary syringe having a nipple at the lower end thereof insertable into the first unattached piston (33) so as to define a space between the end thereof and the top surface of the piston (33).

15 11. A method for performing an enzyme immunoassay, comprising the steps of: attaching an antibody, antigen or hapten to an internal surface of a tube; flowing a test liquid through the tube for about one minute; flowing a first wash solution through the tube to flush out the  
20 test liquid; flowing an enzyme conjugate solution through the tube followed by an incubation period of at least one minute; flowing a second wash solution through the tube at the end of the incubation period to flush out the enzyme conjugate solution; and flowing a solution  
25 containing enzyme substrate and enzyme metabolite indicator through the tube followed by an incubation period of up to about 10 minutes.

12. A method as claimed in claim 11, wherein the enzyme substrate is dissolved just prior to performing  
30 the assay.

13. A method as claimed in claim 11 or 12, wherein human chorionic gonadotropin antibody (anti-HCG) is

attached to the internal surface of the tube, the enzyme conjugate is urease/anti-HCG, the substrate is urea, and the indicator is bromthymol blue.

14. A method as claimed in claim 13, wherein the  
5 test liquid is urine or serum.

1/2

0144162





FIG. 1








FIG. 2




FIG. 3